Version: 1.2 / EN Revision Date: 08/22/2017

SECTION 1: IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

1.1 Product identifiers

Product Name	:	ACS Material Silica-Coated Upconverting Nanoparticles
Brand	:	ACS Material LLC
CAS-No.	:	7681-49-4(Sodium fluoride), 64-17-5(Ethanol)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company	:	ACS MATERIAL LLC 959 E Walnut St., Suite 100 Pasadena, CA 91106
		1 asauena, CA 31100
		USA
Telephone	:	+1 (866)-227-0656
Fax	:	+1 (781)-518-0284

1.4 Emergency telephone number

Emergency Phone #: +1 (866)-227-0656

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification

Flammable liquids (Category 2) Acute toxicity, Oral (Category 2) Skin corrosion/irritation (Category 2) Serious eye damage/eye irritation (Category 2A) Acute aquatic toxicity (Category 3) Specific target organ toxicity - single exposure (Category 3)

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapour.
H300	Fatal if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
	-



Harmful to aquatic life.

Precautionary stateme	nt(s)
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear eye protection/ face protection. Wear protective gloves.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Target Organs

Damage to the heart, liver, nervous system, kidney, bone, gastrointestinal tract, teeth, lungs.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

H402

Substance name Formula	:	ACS Material Silica-Coated Upconverting Nanoparticles NaYREF ₄ (RE: Yb, Er, Tm, Gd, Mn, Lu)@dSiO ₂
Substance Synonyms CAS-No. EC-No. Molecular weight Formula		Ethanol Ethyl alcohol 64-17-5 200-578-6 46.07 g/mol C_2H_6O



Substance CAS-No. EC-No. Molecular weight Formula	: : : :	Sodium fluoride 7681-49-4 231-667-8 41.99 g/mol NaF
Substance Synonyms	:	Silica Silicic anhydride Silicon dioxide
CAS-No. EC-No. Molecular weight Formula	: : :	7681-49-4 231-667-8 60.08 g/mol SiO ₂

Hazardous components

Component	Concentration	CAS-No.
Ethanol	99.9 wt %	64-17-5
Sodium fluoride	< 0.1 wt %	7681-49-4
Yttrium	< 0.1 wt %	7440-65-5
Ytterbium	< 0.1 wt %	7440-64-4
Erbium	< 0.1 wt %	7440-52-0
Thulium	< 0.1 wt %	7440-30-4
Gadolinium	< 0.1 wt %	7440-54-2
Manganese	< 0.1 wt %	7439-96-5
Lutetium	< 0.1 wt %	7439-94-3
Silica	< 0.1 wt %	112945-52-5

For the full text of the phrases mentioned in this Section, see Section 16.

Hazardous impurities: None known.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

In case of skin contact



ACS Material LLC

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.First treatment with calcium gluconate paste.

In case of eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed No data available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Hazards arising from the substance or mixture

Hazardous decomposition products formed under fire conditions. - Carbon oxides, hydrogen fluoride, sodium oxides, yttrium oxides, ytterbium oxides, erbium oxides, gadolinium oxides, manganese/manganese oxides, silicon oxides.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

5.5 Further information

Use water spray to cool unopened containers..

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions



Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

Keep in suitable, closed containers for disposal. For disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store near acids. Hygroscopic. Keep at 4-8 °C. Light, and moisture sensitive.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control Parameters	Basis
Ethanol	64-17-5	TWAEV	1,000.000000 ppm 1,900.000000 mg/m ³	Canada. Ontario OELs
		TWA	1,000.000000 ppm 1,880.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWAEV	1,000 ppm 1,880 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants



ACS Material LLC

1,000.000000	Canada. British Columbia OEL
ppm	
1,000.000000 ppm	Canada. British Columbia OEL
1,000.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
1,000.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
2.500000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Canada. Ontario OELs
2.500000	Canada. British Columbia OEL
2.500000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
V 2.5 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
2.500000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
1 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
1 mg/m ³	Canada. British Columbia OEL
V 1 mg/m ³	Canada. Ontario OELs
V 1 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
1 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
V 1.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
3.000000 mg/m ³	Québec. Regulation respecting occupational health and safety,
	ppm 1,000.000000 ppm 1,000.000000 ppm 2.500000 mg/m ³ 1 mg/m ³ 3.000000



ACS Material LLC

			Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	TWAEV	0.200000 mg/m ³	Canada. Ontario OELs
	TWAEV	5 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	TWA	0.200000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	TWA	0.200000 mg/m ³	Canada. British Columbia OEL
Remarks	Adverse rep	roductive effect.	
	TWA	0.020000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
	TWA	0.100000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
	TWA	0.200000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)

8.2 Exposure controls

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Appropriate engineering controls

Use mechanical exhaust or laboratory fumehood to avoid exposure.

Personal protective equipment

Eye/face protection

Use equipment for eye protection, face shield and safety glasses tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator



ACS Material LLC

cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure Do not let product enter drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

1)	Appearance	Form: Dispersion
		Colour: Ivory white
2)	Odour	Odourless
3)	Odour Threshold	No data available
4)	рН	No data available
5)	Melting point/freezing point	Melting point/range: -114 °C (-173 °F)
6)	Initial boiling point and boiling range	78 °C (172 °F)
7)	Flash point	14.0 °C (57.2 °F) - closed cup
8)	Evaporation rate	No data available
9)	Flammability (solid, gas)	May be combustible at very high temperature
10)	Upper/lower flammability or explosive	Upper explosive limit: 19 %(V)
	limits	Lower explosive limit: 3.3 %(V)
11)	Vapour pressure	59.5 hPa (44.6 mmHg) at 20.0 °C (68.0 °F)
12)	Vapour density	No data available
13)	Relative density	0.789 g/cm ³ at 25 °C (77 °F)
14)	Water solubility	Completely soluble
15)	Partition coefficient: n- octanol/water	log Pow: -0.349 at 24 °C (75 °F)
16)	Auto-ignition temperature	363 °C (685 °F)
17)	Decomposition temperature	No data available
18)	Viscosity	No data available
19)	Explosive properties	No data available
20)	Oxidizing properties	No data available
•		

Other safety information No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available.



9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid**

Heat, spark and flame. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Alkali metals, oxidizing agents, peroxides, strong acids, halogens, oxygen, phosphorus, sulphur oxides, hydrogen fluoride, ammonia, oxygen difluoride, chlorine trifluoride.

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, hydrogen fluoride, sodium oxides, ytterbium oxides, erbium oxides, gadolinium oxides, manganese/manganese oxides, silicon oxides.

Other decomposition products - Gaseous hydrogen fluoride (HF). In the event of fire: see section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50: No data available. LC50: No data available. Dermal: No data available. Intravenous - Rat - Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

Skin corrosion/irritation

Irritating to skin.

Serious eye damage/eye irritation

Eyes - Rabbit - Moderate eye irritation.

Respiratory or skin sensitisation No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

Carcinogenicity - Mouse – Oral Carcinogenicity - Rat - Intramuscular

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors.

Blood: Lymphomas including Hodgkin's disease.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity



Reproductive toxicity - Human - female - Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on Newborn: Drug dependence.

Specific target organ toxicity - single exposure No data available.

Specific target organ toxicity - repeated exposure No data available.

Aspiration hazard

No data available.

Potential health effects

Inhalation	May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Ingestion	May be fatal if swallowed. Aspiration hazard if swallowed – can enter lungs and cause damage.
Skin	May be harmful if absorbed through skin. May cause skin irritation.
Eyes	Causes eye irritation.

Signs and Symptoms of Exposure

Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia. Rare earth compounds may cause delayed blood clotting leading to hemorrhages. Inhalation of rare earths may cause sensitivity to heat, itching, and increased awareness of odor and taste.

Additional Information

RTECS: KQ6300000(Ethanol).

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

No data available.

- **12.2 Persistence and degradability** No data available.
- **12.3 Bioaccumulative potential** Bioaccumulation - Salmo trutta
- **12.4 Mobility in soil** No data available.
- 12.5 Results of PBT and vPvB assessment



No data available.

12.6 Other adverse effects

Harmful to aquatic life.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

SECTION 14: TRANSPORT INFORMATION

UN number ADR/RID: 1170	IMDG: 1170	IATA: 1170		
UN proper shipping name ADR/RID: Ethanol. IMDG: ETHANOL. IATA: Ethanol.				
Transport hazard class(es) ADR/RID: 3 IMDG: 3		IATA: 3		
Packaging group ADR/RID: - IMDG: - IATA: -				
Environmental hazards ADR/RID: no IMDG Marine pollutant: no IATA: no				
Special precautions for user				

No data available.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Authorisations and/or restrictions on use WHMIS Classification



Safety	ACS Material	
B2	Flammable liquid	Flammable liquid
D1B	Toxic Material Causing Immediate and Serious Toxic Effects	Toxic by ingestion
D2A	Very Toxic Material Causing Other Toxic Effects	Reproductive hazard
D2B	Toxic Material Causing Other Toxic Effects	Moderate skin irritant Moderate eye irritant
		,

SECTION 16: OTHER INFORMATION

HMIS Classification	
Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard:	0

Disclaimer: ACS Material, LLC believes that the information in this Safety Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties either express or implied, regarding the suitability of the material for any purpose or the accuracy of the information contained within this document. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.

LLC